



339.00 EUR  
incl. 19% VAT, plus [shipping](#)

- Intel Elkhart Lake SoC !
- 2x LAN !

- Intel Elkhart Lake SoC Processor
- 1\* DDR4 3200MHz SO-DIMM up to 32GB
- 1\* HDMI, 2\* USB3.1, 1\* USB-C, 2\* RJ45, 1\* COM
- Support 9~36V wide voltage input
- DC12V\_40W Adapter

|                    |                                                                                                                                                                          |  |
|--------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|
| Model              | <ul style="list-style-type: none"> <li>– HBFBP01-6210-B</li> <li>– HBFBP01I-6210-B (WiFi model)</li> </ul>                                                               |  |
| CPU/Chipset        | – Intel® Elkhart Lake SoC Processor                                                                                                                                      |  |
| BIOS               | – AMI Flash ROM                                                                                                                                                          |  |
| Memory             | – 1* DDR4 3200MHz Dual Channel SO-DIMM up to 32GB                                                                                                                        |  |
| Storage            | – 1* M.2 M-key (2242, PCIe Gen.3 x2/SATA interface) support NVMe                                                                                                         |  |
| Expansion          | – 1* M.2 E-key (2230, PCIe Gen.3 x1/USB2.0 interface)                                                                                                                    |  |
| Rear Panel I/O     | <ul style="list-style-type: none"> <li>– 2* RJ45</li> <li>– 1* DC-in</li> <li>– 1* HDMI</li> <li>– 2* USB3.1(Gen.2) A Type</li> <li>– 1* USB3.1(Gen.2) C Type</li> </ul> |  |
| Front Panel I/O    | <ul style="list-style-type: none"> <li>– 1* Power button + Power LED</li> <li>– 1* RS232/422/485</li> </ul>                                                              |  |
| Internal Connector | <ul style="list-style-type: none"> <li>– 1* GPIO</li> <li>– 2* USB2.0</li> </ul>                                                                                         |  |
| Power Source       | <ul style="list-style-type: none"> <li>– Adapter : AC 90~240V input / DC12V_40W output / Lock type</li> <li>– System : DC9~36V input support</li> </ul>                  |  |
| Compliance         | – CE, FCC, LVD, RoHS, ErP Ready                                                                                                                                          |  |
| Dimensions         | <ul style="list-style-type: none"> <li>– System: 125 (W) x 109 (D) x 44.5 (H) mm</li> <li>– Color Box : 158 (W) x 167 (D) x 123.6 (H) mm</li> </ul>                      |  |

|             |                                                                                                                                                                                                                                          |
|-------------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Temperature | <ul style="list-style-type: none"><li>– Operating Temperature: -20 ~ 60° C (Under the condition of using M.2 interface SSD)</li><li>– Storage Temperature: -40 ~ 85° C</li><li>– Humidity: 10% ~ 95% RH @40°C (non-condensing)</li></ul> |
| OS Support  | <ul style="list-style-type: none"><li>– Windows 11, Linux</li></ul>                                                                                                                                                                      |